


13A Unswitched Fuse - Traditional Plate







TECHNICAL SPECIFICATION

Standard(s) BS 1363-4 Voltage Rating 13 Amp, 250V° Contact Gap Normal Gap Mounting Box Depth (Min) 25mm Terminal Capacity 3 x 2.5mm², 3 x 4.0mm², 2 x 6.0mm² (L&N) Earth Terminal Capacity 3x 2.5mm², 2 x 4.0mm², 1 x 6.0mm² (Earth) Fixing Centres 60.3mm Size 86mm x 86mm x 4.5mm (Plate thickness) Product Class 1 Face plate must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m IP Rating IP2XD Mains Frequency 50hz - 60hz Contact Gap Minimum 3mm Trademarks		
Contact Gap Normal Gap Mounting Box Depth (Min) 25mm Terminal Capacity 3 x 2.5mm², 3 x 4.0mm², 2 x 6.0mm² (L&N) Earth Terminal Capacity 3x 2.5mm², 2 x 4.0mm², 1 x 6.0mm² (Earth) Fixing Centres 60.3mm Size 86mm x 86mm x 4.5mm (Plate thickness) Product Class 1 Face plate must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m IP Rating IP2XD Mains Frequency 50hz - 60hz Contact Gap Minimum 3mm	Standard(s)	BS 1363-4
Mounting Box Depth (Min) Terminal Capacity 3 x 2.5mm², 3 x 4.0mm², 2 x 6.0mm² (L&N) Earth Terminal Capacity 3 x 2.5mm², 2 x 4.0mm², 1 x 6.0mm² (Earth) Fixing Centres 60.3mm Size 86mm x 86mm x 4.5mm (Plate thickness) Product Class 1 Face plate must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m IP Rating Mains Frequency 50hz - 60hz Contact Gap Minimum 3mm	Voltage Rating	13 Amp, 250V [~]
Terminal Capacity 3 x 2.5mm², 3 x 4.0mm², 2 x 6.0mm² (L&N) Earth Terminal Capacity 3x 2.5mm², 2 x 4.0mm², 1x 6.0mm² (Earth) Fixing Centres 60.3mm Size 86mm x 86mm x 4.5mm (Plate thickness) Product Class 1 Face plate must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m IP Rating IP2XD Mains Frequency 50hz - 60hz Contact Gap Minimum 3mm	Contact Gap	Normal Gap
Earth Terminal Capacity 3x 2.5mm², 2 x 4.0mm², 1 x 6.0mm² (Earth) Fixing Centres 60.3mm Size 86mm x 86mm x 4.5mm (Plate thickness) Product Class 1 Face plate must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m IP Rating IP2XD Mains Frequency 50hz - 60hz Contact Gap Minimum 3mm	Mounting Box Depth (Min)	25mm
Fixing Centres 60.3mm Size 86mm x 86mm x 4.5mm (Plate thickness) Product Class 1 Face plate must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m IP Rating IP2XD Mains Frequency 50hz - 60hz Contact Gap Minimum 3mm	Terminal Capacity	3 x 2.5mm², 3 x 4.0mm², 2 x 6.0mm² (L&N)
Size 86mm x 86mm x 4.5mm (Plate thickness) Product Class 1 Face plate must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m IP Rating IP2XD Mains Frequency 50hz - 60hz Contact Gap Minimum 3mm	Earth Terminal Capacity	3x 2.5mm², 2 x 4.0mm², 1 x 6.0mm² (Earth)
Product Class 1 Face plate must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m IP Rating IP2XD Mains Frequency 50hz - 60hz Contact Gap Minimum 3mm	Fixing Centres	60.3mm
Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m IP Rating IP2XD Mains Frequency 50hz - 60hz Contact Gap Minimum 3mm	Size	86mm x 86mm x 4.5mm (Plate thickness)
Recommended Location Internal Use Only Maximum Installation Altitude 2000m IP Rating IP2XD Mains Frequency 50hz - 60hz Contact Gap Minimum 3mm	Product Class 1	Face plate must be earthed
Maximum Installation Altitude2000mIP RatingIP2XDMains Frequency50hz - 60hzContact Gap Minimum3mm	Ambient Operating Temperature	-5° to +40°C
IP Rating IP2XD Mains Frequency 50hz - 60hz Contact Gap Minimum 3mm	Recommended Location	Internal Use Only
Mains Frequency 50hz - 60hz Contact Gap Minimum 3mm	Maximum Installation Altitude	2000m
Contact Gap Minimum 3mm	IP Rating	IP2XD
	Mains Frequency	50hz - 60hz
Trademarks	Contact Gap Minimum	3mm
	Trademarks	